| | DUCATI SCRAMBLER |
|-------------------------|---|
| Engine | |
| Туре | L-Twin, Desmodromic distribution, 2 valves per cylinder, air cooled |
| Displacement | 803 cc |
| Bore x Stroke | 88 x 66 mm |
| Compression Ratio | 11:1 |
| Power | 75 hp (55 kW) 8250 rpm |
| Torque | 50 lb-ft (68 Nm) @ 5750 rpm |
| Fuel injection | Electronic fuel injection, 50 mm throttle body |
| Exhaust | Exhaust system with single stainless steel muffler with aluminium exterior cover, catalytic converter and 2 lambda probes |
| Emissions | Euro 3 |
| Transmission | |
| Gearbox | 6 speed |
| Ratio | 1=32/13 2=30/18 3=28/21 4=26/23 5=22/22 6=24/26 |
| Primary drive | |
| Final drive | Straight cut gears, Ratio 1.85:1 |
| Clutch | Chain, front spocket 15, rear sprocket 46 |
| | APTC wet multiplate with mechanical control |
| Chassis | |
| Frame | Tubular steel Trellis frame |
| Wheelbase | 1445 mm (56.9 in) |
| Rake | 24° |
| Trail | 112 mm (4.4 in) |
| Total steering lock | 35° |
| Front suspension | Upside down Kayaba 41 mm fork |
| Front wheel travel | 150 mm (5.9 in) |
| Front wheel | 10-spoke in light alloy 3.00" x 18" |
| Front tyre | 110/80 R18 Pirelli MT 60 RS |
| Rear suspension | Kayaba rear shock, pre-load adjustable |
| Rear wheel travel | 150 mm (5.9 in) |
| Rear wheel | 10-spoke light alloy 5.50" x 17" |
| Rear tyre | 180/55 R17 Pirelli MT 60 RS |
| Front brake | Single 330 mm disc, radial 4-piston calliper with ABS as standard equipment |
| Rear brake | 245 mm disc, 1-piston floating calliper with ABS as standard equipment |
| Fuel tank capacity | 13.5 I - 3.57 gallon (US) |
| Dry weight | 170 kg (375 lb) |
| *Wet weight | 186 kg (410 lb) |
| Seat height | 790 mm (31.1 in) - low seat 770 mm (30.3 in) available as accessory |
| Max height | 1150 mm (45.3 in) (brake reservoir) |
| Max width | |
| | 845 mm (33.3 in) (mirrors) |
| Max length | 2100 - 2165 mm (82.7 - 85.2 in) |
| Instrumentation | LCD |
| Ducati electronics | dual-channel ABS |
| Warranty | 2 years unlimited mileage |
| Versions | Dual seat |
| All versions equipment | Steel tank with interchangeable aluminium side panels, headlight with glass lens, LED light-guide and interchangeable aluminium cover, LED rear light with diffusive lens, LCD instruments with interchangeable aluminium cover, machine-finished aluminium belt covers, 18" front, 17" rear wheels, underseat storage compartment with USB socket |
| Urban Enduro equipment | Spoked aluminium wheels, aluminium engine sump guard, high front mudguard, headlight grill, aluminium handlebar crossbrace, front stem protectors, seat with dedicated design, dedicated logo |
| Full Throttle equipment | Termignoni slip-on silencer, low aluminium handlebars, flat-track style seat, sport tail piece with dedicated turn indicator support, sport style front mudguard, black fuel tank side covers, dedicated logo |
| Classic equipment | Spoked aluminium wheels, front and rear aluminium mudguards, seat with dedicated design, fuel tank with black stripe, dedicated logo, high plate support |

*Wet weight

Wet weight includes all fluids and fueled to at least 90% of useable tank capacity. (93/93/CE)